


UTILITY ROCK RIPPER




AUGERS | 104" Overall Length

ITEM	DIA	NO. TEETH	LBS	2" HEX	2 1/2" HEX	2 5/8" HEX
9-MRR-10460	9"	8	200	101150	133600	101151
10-MRR-10460	10"	9	225		134705	
12-MRR-10460	12"	10	250	101152	133601	101153
16-MRR-10460	16"	13	300	101154	133602	101155
18-MRR-10460	18"	14	340	101156	133603	101157
20-MRR-10460	20"	16	360	101158	133604	101159
22-MRR-10460	22"	17	390		101679	102898
24-MRR-10460	24"	19	420	101160	133605	101161
30-MRR-10460	30"	23	470	101162	133606	101163
36-MRR-10460	36"	27	500	101164	133615	101165



PARTS | Pilot Bits



ROCK RIPPER

THE NUTS & BOLTS:

Included with the RRP 1.75 SQ Pilot. When purchased individually, this pilot ships with four STRATA® SR-76SW conical teeth.

RRP 1.75 SQ	
Rock pilot for use in hard, fractureable rock	
LBS 15	
PN 137208	
Use 1.75SQ Adapter PN 137203	

PARTS | Teeth



Strata Drilling Grade Conical Teeth were developed by Pengo for the Drilling industry.

STRATA
DRILLING GRADE CONICAL

STRATA® SR-76SW	
LBS .7	
PN 850035	



SRLO8	
LBS .5	
PN 850032	

P-10 Pocket	
.86 Shank pocket for PRL-08 and SR-76SW Conical Teeth	
LBS .8	
PN 990043	

ACCESSORIES:

To prevent carbide on conical teeth from breaking, Pengo highly recommends using a soft hammer during installation of bullet teeth.



Soft Hammer	
LBS 3.5	
PN 137737	



C30 Puller	
LBS 3	
PN 134090	



C123 Puller	
LBS 3	
PN 134091	

Due to the enlarged shoulder of the SR-76SW Strata® Tooth, the C30 Puller is recommended to aid in removing the tooth.

The S-RL08 Teeth will need the C123 Puller for removal.